

DYNAMIX

TWO-TONE METALLIC EFFECT



DESCRIPTION

Dynamix is a decorative finish that gives depth and dimension to your interiors through a two-toned, metallic, and pearlescent texture obtained by simultaneously applying two Dynamix shades.

RECOMMENDED FOR

Interior applications on plaster, gypsum board, and other properly prepared and primed substrates.

KEY FEATURES

- Layered surface that combines sandy and smooth textures
- Two-tone colors
- Contains particles that shimmer with light
- Odorless
- Water based
- Low VOC

PHYSICAL PROPERTIES

Solvent Type	Waterborne
Finish Type	Variegated
Spreading Rate	Approximately 18 m ² /kg/coat/color reference – 1 coat required
Average Dry Time	15 minutes - 1 hour based on ASTM D 1640
Recoat	After 2 – 4 hours, a 2 nd coat can be applied but usually not desired
Flash Point	Not Applicable
Dry Film Thickness	100 – 200 microns depending on application technique
Thinner	No thinning is required
Adhesion	Classified 4B based on ASTM 3359-B for excellent adhesion
Density	1.40 ±0.05 g/cm ³
%Solids (Volume)	35 %
Viscosity	80,000 – 90,000 (Spindle 6/Speed 8) based on ASTM D2196
VOC	26 g/L VOC content - Compliant with EU 2010 regulations maximum of 30 g/L.
Additives	Colortek Deco Additives (1,2,3, 4,5,6,7,8,9,10)

SURFACE PREPARATION

All surfaces must be cured, clean, dry, and free from dirt, dust, rust, stains, grease, oil, mildew, wax, efflorescence, bond-breakers and other contaminants. Remove all loose, peeling, or chalky paint by sanding, scraping, or any other appropriate methods. Repair all cracks, holes, and other surface imperfections with a suitable patching material. Repaired surfaces should then be sanded smooth, dusted clean and primed with a suitable Colortek primer.

New plaster or masonry surfaces must be allowed to cure (28 days) before applying base coat. Cured plaster should be hard, have a slight sheen and maximum pH of 10; soft, porous or powdery plaster indicates improper cure. Knife off any protrusions and prime the plaster before and after applying patching compound. Poured or pre-cast concrete with a very smooth surface should be etched or abraded to promote adhesion, after removing all form release agents and curing compounds. Remove any powder or loose particles.

CAUTION: Scraping or sanding surfaces of older buildings may release dust containing lead or asbestos. **EXPOSURE TO LEAD OR ASBESTOS CAN BE VERY HAZARDOUS TO YOUR HEALTH.** Always wear appropriate personal protective equipment during surface preparation and finish clean-up of any residues by water-washing all surfaces.

COLORTEK®
Wall and Floor Fashion

info@colortek.eu
www.colortek.eu



DYNAMIX

TWO-TONE METALLIC EFFECT



PRIMER SYSTEMS

SURFACE TYPE	RECOMMENDED COLORTEK PRIMER
Drywall	Colortek Primer
Porous Masonry	Colortek Sealer, Colortek Primer
Non-Porous Masonry	Colortek Primer, Colortek Undercoat
Wood	Colortek Undercoat or Colortek Wood Primer
Metal	Colortek Adhero, Adhero Quick Dry, SX47 StopRust, AquaZinc

APPLICATION CONDITIONS

Do not apply at temperatures below 5 °C or when rain is expected.

APPLICATION METHOD

- Apply one coat of Dynamix Primer and leave surface to dry.
- Deposit small amounts of Dynamix on the wall using a double-headed brush (a specialty brush consisting of two identical brush heads).
- Make sure to only dip the brush tip and to apply in a crisscross fashion while rotating the double headed brush on its axis.
- Do not mix the deposited material immediately. Move across the wall and only go back over the edges to unify the strokes once the paint has slightly dried.
- Using a clean normal decorative brush (with no handle), go over the surface still partly wet in a crisscross manner to spread the particles and create the Dynamix unique pattern.

PACK SIZE

- 1 US Quart – 1 kg

SHELF LIFE

24 months from the date of production.

STORAGE AND HANDLING

Care should be taken to avoid spillage. Store in a dry area. Protect from freezing. Extreme temperatures may cause paint to become unusable. For example: freezing and thawing may cause paint to gel, and high heat may cause solid skin to form.

SAFETY

Use under well ventilated conditions. Do not breathe or inhale spray mist or sanding dust. Avoid skin contact; spillage on the skin should immediately be removed with suitable cleanser, soap and water. In case of eye contact, flush immediately with water for at least 15 minutes and seek medical attention immediately. If you experience difficulty breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately.

CLEANING

Remove as much leftover product as possible from the application equipment before cleaning. Clean equipment immediately after use with warm soapy water and rinse thoroughly. Do not empty product into drains or watercourses.

TECHNICAL ASSISTANCE

Available through your local COLORTEK® Design Center or through your COLORTEK PAINTS® authorized distributor. For the location of the retailer nearest you, email us at info@colortek.eu or check our website www.colortek.eu.

DISCLAIMER

Product batches are subject to stringent quality control checks in conformity with ISO 9001:2015, Certificate LB18/234269.

The information submitted in this manual is correct to the best of our knowledge & experience. No liability whatsoever can be accepted on the basis of the information supplied herein.