

# V-Lux 850

## HIGH BUILD METALLIC DECORATIVE FINISH



### DESCRIPTION

V-Lux 850 is a luxurious interior decorative coating designed to exude elegance and sophistication with its creative patterns, color blends and splendor textures.

### RECOMMENDED FOR

High build interior and exterior decorative applications.

### KEY FEATURES

- Metallic silver shade
- High build
- No lead
- Made from eco-friendly raw material
- Low VOC
- Greenguard Gold compliant

### PHYSICAL PROPERTIES

<b>Solvent Type</b>	Waterborne
<b>Spreading Rate</b>	Approximately 3-4 m <sup>2</sup> /kg/ coat – 2 coat required to achieve the effect as per the catalogue
<b>Thinner</b>	None required
<b>Drying Time</b>	Touch Dry after 4 - 5 hours at 20°C / Completely dry after 24 hours at 20°C
<b>Specific Weight</b>	1.0 at 20°C
<b>Viscosity</b>	200000-250000 cP at 23 °C (spindle 7/speed 6)
<b>Base</b>	850/00 Fog

### SURFACE PREPARATION

All surfaces must be cured, clean, dry, and free from dirt, dust, rust, stains, grease, oil, mildew, wax, efflorescence, bond-breakers and other contaminants. Remove all loose, peeling, or chalky paint by sanding, scraping, or any other appropriate methods. Repair all cracks, holes, and other surface imperfections with a suitable patching material. Repaired surfaces should then be sanded smooth and dusted clean. Rub & prime for wood surfaces with a suitable Colortek Primer.

New plaster or masonry surfaces must be allowed to cure (28 days) before applying base coat. Cured plaster should be hard, have a slight sheen and a maximum pH of 10. A soft, porous or powdery plaster indicates improper cure. Never sand a plaster surface; knife off any protrusions and prime plaster before and after applying patching compound. Poured or pre-cast concrete with a very smooth surface should be etched or abraded to promote adhesion, after removing all form release agents and curing compounds. Remove any powder or loose particles.

**CAUTION:** Scraping or sanding surfaces of older buildings may release dust containing lead or asbestos. EXPOSURE TO LEAD OR ASBESTOS CAN BE VERY HAZARDOUS TO YOUR HEALTH. Always wear appropriate personal protective equipment during surface preparation and finish cleanup of any residues by water-washing all surfaces.

### PRIMER SYSTEMS

<b>Drywall</b>	Colortek Primer
<b>Porous Masonry</b>	Colortek Sealer, Colortek Primer
<b>Non-Porous Masonry</b>	Colortek Primer or Colortek Undercoat
<b>Wood</b>	Colortek Undercoat or Colortek Wood Primer
<b>Metal</b>	Colortek Adhero, Adhero Quick Dry, SX47 StopRust, AquaZinc

**COLORTEK®**

Wall and Floor Fashion

[info@colortek.eu](mailto:info@colortek.eu)

[www.colortek.eu](http://www.colortek.eu)



# V-Lux 850

## HIGH BUILD METALLIC DECORATIVE FINISH



### APPLICATION CONDITIONS

Do not apply at temperatures below 5 °C or when rain is expected

### APPLICATION METHOD

- Apply 2 coats of C1C colored on the properly primed and cleaned surface.
- Apply V-lux in an irregular manner, using an inox trowel and pass it back over the surface by troweling it horizontally and vertically.
- After fully dry, apply a second coat of a different color of V-Lux in the same manner.
- Apply Colortek Dark Matter Varnish to give the dead flat effect.

### PACK SIZE

- 1 US Gallon 2.4 Kg
- 1 US Quart 0.8 Kg

### SHELF LIFE

24 months from the date of production.

### STORAGE AND HANDLING

Care should be taken to avoid spillage. Store in a dry area. Protect from freezing. Extreme temperatures may cause paint to become unusable. For example: freezing and thawing may cause paint to gel, and high heat may cause solid skin to form.

### SAFETY

Use under well ventilated conditions. Do not breathe or inhale spray mist or sanding dust. Avoid skin contact; spillage on the skin should immediately be removed with suitable cleanser, soap and water. In case of eye contact, flush immediately with water for at least 15 minutes and seek medical attention immediately. If you experience difficulty breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately.

### CLEANING

Remove as much leftover product as possible from the application equipment before cleaning. Clean equipment immediately after use with mineral spirits or paint thinner. Do not empty product into drains or watercourses. Wash hands after use in warm soapy water.

### TECHNICAL ASSISTANCE

Available through your local COLORTEK® Design Center or through your COLORTEK PAINTS® authorized distributor. For the location of the retailer nearest you, email us at [info@colortek.eu](mailto:info@colortek.eu) or check our website [www.colortek.eu](http://www.colortek.eu).

### DISCLAIMER

Product batches are subject to stringent quality control checks in conformity with ISO 9001:2008, Certificate CH12/1128.

The information submitted in this manual is correct to the best of our knowledge & experience. No liability whatsoever can be accepted on the basis of the information supplied herein.